Website : www.bbmchandikhole.org
E-mail : principal_bbm_ckl12@yahoo.in
bbmprincipal@gmail.com
Fax : +916725226288 Tel. : 06725-226288

BABA BHAIRABANANDA AUTONOMOUS MAHAVIDYALAYA
CHANDIKHOLE, DIST- JAJPUR, ODISHA, PIN- 755044

Letter No. 1249/26. Date 10.11.2026

CORRIGENDUM

Sub: Corrigendum to Tender No. 202575559760/2026-27/001 for Supply, Installation and Commissioning of Desktop Computer, UPS & MFM Printer

The Schedule of Tender issued on 06/11/2026 refers to "Quantity to be supplied: As per Annexure I". Annexure-I was inadvertently left out of the tender document. It is hereby added, as given below, and forms part of the tender document.

10.11.26

For Principal
B.B. (Auto.) Mahavidyalaya
Chandikhole

Principal
B.B. (Auto) Mahavidyalaya
Chandikhole, Jajpur

ANNEXURE – I

Sl. No. 1 — All-in-One Desktop Computer

Quantity: 08

Chipset Series	Intel Q series
Chipset Number	Intel Q670
Expansion Slot (Mdot 2)	2 or Higher
Processor	
Processor Make	Intel
Processor Generation	14
Processor Base Frequency (GHZ)	2.5 or Higher
Number of cores per processor	10 or higher
Processor Description	Intel Core i5 or higher
Processor Number	Intel Core i5 14500 or higher
Out of band management	NA
Cache (MB)	24
Graphics	
Graphic Type	Integrated
Graphic card description	UHD graphics
Size of memory in case of Dedicated Graphic Card (GB)	0
Size of VRAM in case of Dedicated Graphics (MB)	0
Operating System (Factory Pre-loaded)	Windows 11 Professional
Recovery Image Media	CD from the OEM Stored in partition of Hard disk/USB Drive from the OEM/Online cloud
OS Certification	Windows
Memory	
Type of RAM	DDR5
RAM Size (GB)	16
RAM Speed (MHz)	4800
Total number of DIMM Slots available	4
No. of DIMM Slots Populated	2
RAM Expandability	64
Storage	
Type of Drives used to populate the Internal Bays	SSD
Number of Internal Bays Populated with HDD	0
Capacity of each HDD	N/A

Total HDD Capacity (GB)	0
Number of Internal Bays Populated with SSD	1
Capacity of each SSD (GB)	512
Total SSD Capacity (GB)	512
Optane Memory	0
Display	
Display Size	23.8
Display Type	Non Touch
Pannel Technology	IPS/TN/VA
Display Resolution	1920*1080
Availability of web Cam integrated with Display	yes
If Yes, resolution of Web Cam	FDD
Availability of speakers integrated with display	Yes
If Yes, Speakers available	2
Connectivity	
Wireless connectivity	Yes
If Yes, Type of wireless connectivity	Wifi-6
No. of Ethernet ports	1
Type of Ethernet ports	10/100/1000 on board integrated gigabit ports
Bluetooth Connectivity	Yes
If Yes, Version of Bluetooth available	Bluetooth version 5.3
Ports	
No. of USB Version 2.0 ports	0
No. of USB Version 3.2, Gen 1 ports	2 or higher
No. of USB Version 3.2, Gen 2 ports	3 or higher
No. of USB type c ports	1 or higher
No. of serial ports	0
No. of VGA ports	0
No. of HDMI ports	1
No. of DP ports	1
Generic	
Optical drive	N/A
Audio In	Yes
Audio out	Yes
Headphone out	Yes
Microphone in	Yes, Dual Array

Stand	Height adjustable
Power	
Power supply	Internal (Without any adaptor)
Power supply capacity (Watt)	150 or higher
Minimum power efficiency	85 to 90
Certification	
BIS Registration	Yes
RoHS Compliance	Yes
BEE Energy Star for given model	Yes
Other certification	TCO-UL, FCC, CE, ISO-9001, 14001, 27001/20001
Mouse & Keyboard	
Mouse Connectivity	Wired
Type of Mouse	Optical Scroll
Keyboard Connectivity	Wired
Type of Keyboard	Standard
Operating Conditions	
Minimum Operating Temperature	5 degree Celsius
Maximum Operating Temperature	35 degree Celsius
Minimum Operating humidity	5
Maximum Operating humidity	90
Warranty	
Onsite OEM Warranty	5 years
OS Certification	Windows & UBUNTU/Red Hat/ SUSE/ Linux

Sl. No. 2 — UPS (600 VA UPS)

Quantity: 08

Parameter	Minimum Specifications
Capacity	600 VA or more, Line Interactive
Technology	Automatic Voltage Regulation
Input Frequency range	50Hz +/- 5%
Output Frequency Range	50Hz +/- 5%
Input Voltage	160V - 280V, Single Phase AC
Output Voltage	180 VAC - 250 VAC +/- 10%
Voltage Regulation	+/- 10% (or better)
Output waveform	Modified Sine Wave
Output Power Factor	0.6 or More
Battery Type	SMF-VRLA Built-in, Minimum Vah should be 84 Vah
Battery Make	Exide/ Quanta/ Uplus/NED/Panasonic/Yuasa/Rocket (Battery)
Battery Backup	Minimum backup of 15 minutes
Operating Temperature	0 to 40 degree Celsius
Alarms and Indications	All necessary alarms & indications essential for performance monitoring of UPS like mains presence or fail, UPS mode, Low battery, Overload. If input voltage goes outside the range 160V-280V, the system shall switch over to UPS mode. Over voltage, short circuit and overload at UPS output terminal, no load shut down. Under voltage at battery terminal, Battery over charge.
Protections	It should protect from input voltage variation
Certifications	BIS certified at the time of bidding
Warranty of UPS and Battery	The UPS warranty must be 3 years. During the contract, bidder has to ensure the battery life to provide required backup time & during the contract period, as when required, bidder has to replace the batteries without additional cost to the tenderer. Batteries support must be up to 3 years.
Certifications	BIS, ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, ISO 20000-1:2011, ISO 27001:2013, ISO 50001:2018

Revised Specification of Hardware and Microsoft Office with ATC

Web Support	It is mandatory to provide online centralized call tracking system like OVSD (Open View Service Desk) for monitoring of logged calls, viewing through web / windows based access for at least 2 officials.

Sl. No. 3 — Multi-Function Printer

Quantity: 1

Printer type with warranty	Multifunction Machine Printer with Minimum 1 Year On Site Warranty, including Cartridge and Power Cord/Adapter
Core Function	Print, Scan and Copy
Print Technology	Inkjet
Type of Printing	Colour
Print Paper Size	A4, A3 and Legal
Operating System Compatibility	Windows 10 and Above, Linux, Mac OS, Windows Server
Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Monochrome (Black) (in PPM)	21 to 25
Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour (in PPM)	21 to 25
Maximum Scan Area (Platen/Flatbed Size)	A4, A3 and Legal
A4 Scan Speed - Colour (Image Per Minute) @ 300 x 300 dpi	11 to 15
A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dpi	11 to 15
Auto Duplexing Printing/Copying (2-sided Feature)	Yes
Original Document Feeder Type (For Scanning and Copying)	Reverse Duplex Automatic Document Feeders (RADF/DADF)
Number of Paper Tray	2
Connectivity	USB Port, Ethernet Port, Wi-Fi